


2. SPECIFICATIONS AND ACCESSORIES

2-1. SPECIFICATIONS

Specifications			Models	TM-231A	TM-231E	TM-431A (U.S.A. version)	TM-431A/431E	TM-531A	TM-531E	
General	Frequency range		[MHz]	144 to 148	144 to 146	438 to 450	430 to 440	1240 to 1300		
	Mode			F3E (FM)						
	Antenna impedance			50 Ω						
	Power requirements			13.8 VDC ± 15% (11.7 to 15.8)						
	Ground			Negative						
	Frequency stability			Less than ± 10 ppm						
	Current drain	Transmit mode		Less than 11 A				Less than 9.5 A		Less than ± 3 ppm
		Receiver mode with no signal						Less than 0.6 A		Less than 5.5 A
	Operating temperature			- 20 °C to + 60 °C (- 4 °F to + 140 °F)						
	Dimensions (W×H×D) (Projection included)		[mm]	140×40×160 (5-1/2"×1-37/64"×6-19/64") (141×42×171 (5-9/16"×1-21/32"×6-47/64"))						
	Weight		[kg]	1.2 (2.65 lbs)						
Transmitter	Output power*	HI	50 W		35 W		10 W			
		MID	10 W		10 W		—			
		LOW	Approx. 5 W		Approx. 5 W		1 W			
	Modulation			Reactance modulation						
	Spurious radiation			Less than - 60 dB						
	Maximum frequency deviation			± 5 kHz						
	Audio distortion (at 60% modulation)			Less than 3% (300 to 3000 Hz)						
Microphone impedance			500 to 600 Ω							
Receiver	Circuitry			Double conversion superheterodyne						
	Intermediate frequency		1st/2nd	10.7 MHz/455 kHz		30.825 MHz/455 kHz		59.7 MHz/455 kHz		
	Sensitivity (12 dB SINAD)			Less than 0.16 μV						
	Selectivity	- 6 dB		More than 12 kHz						
		- 60 dB		Less than 24 kHz						
	Squelch sensitivity			Less than 0.1 μV						
	Output (5% distortion)			More than 2 W across 8 Ω loads						
External speaker impedance			8 Ω							

- Notes:**
1. Circuit and ratings are subject to change without notice due to advancements in technology.
 2. * Recommended duty cycle: 1 minute Transmit, 3 minutes Reception.

8-2. TM-431A/431E BLOCK DIAGRAM



Note: _____
Circuit is subject to change without notice due to advancements in technology.